

For use in NDT and
security environment

Order No. AP7300

Portable battery- operated X-ray unit **Golden Engineering XRS-4**

The battery-operated X-ray generator XRS-4 is suited for radiological examination of various materials for industry, security sector, military and law enforcement and has a far greater penetration capacity in comparison with earlier models.

The 370 kV generator penetrates more than 3.8 cm (1.5 inches) of steel. With a weight of only 10.5 kg, this makes the XRS-4 a heavy hitter in its weight class. In addition, the X-ray generator sports a robust aluminum case.

It is also possible to change the pulse frequency of the machine and set several pulse sequences with corresponding pauses.

- Max. Output 370 kV
- 4.0 mR - 7.0 mR per pulse
- Pulse rate: 10 pulse per second
- Max. 3.000 pulses / hour
- X-ray pulse width approx. 50 nanoseconds
- Focus 3.0 x 3.0 mm
- Power 220 - 240 V
- Dimensions 445 x 135 x 216 mm
- Weight 9.5 kg (including battery)
- 12 month manufacturer warranty



Portable battery-operated X-ray unit Golden Engineering XRS-4

Scope of supply

- X-ray machine Golden Engineering XRS-4
- Carrying case, remote cord
- 2x battery and 1x battery charger (220 V)

Spezification

Size (without battery pack)	Height 7.91" (20.09 cm) Width 5.43" (13.79 cm) Length 17.43" (44.27 cm)
Weight (Including battery pack)	22 lb / 10.5 kg
Output dose	4.5 to 7 mR/pulse measured 12" from source
Pulse rate	9 pulses per second
X-ray source size	1/8" (3 mm)
Maximum photon energy	370 kVP
X-ray pulse width	10 nanoseconds
Current draw	17 A
Power supply	DeWalt® DC9096 18v Battery
Number of pulses per battery charge	4000
Temperature range	-10 to 120 degrees F (-23 to 50 degrees C)
Maximum duty cycle	200 pulses per 4 minutes
Warm-up	None required
Beam angle	40 degree standard 60 degree available
Warranty	1 year



Please visit www.or-technology.com
for more details

Specifications subject to revision without notice

The editor strives to impart correct and up to date information. The provided specifications are based on current knowledge and are subject to revision without notice. This brochure is subject to correction. The editor assumes no responsibility for the information being up to date, correct and complete. All furnished logos, pictures and graphics are property of the particular company and subject to copyright of the licensor. Use, dissemination, distribution or copying of the pictures, logos or text compiled or processed by the editor is subject to our written consent. All rights reserved.

