

For use in veterinary medicine,
NDT and security sector

Order No. AP2200

Small, battery- operated X-ray unit **Gierth** **TR 90/20 Battery**

Unrestricted freedom for X-raying:

The GIERTH TR 90/20 Battery guarantees unlimited mobility and is the ideal companion for outdoor X-ray applications. With a fully charged battery, you can take up to 300 X-rays completely of grid. A serial interface for connecting to the digital system and easy operation are additional advantages of this X-ray unit. The GIERTH TR 90/20 Battery is delivered in a practical carrying case.



- Battery operated HF X-ray unit with pulse frequency modulation
- Total weight: 6,800 g (battery included)
- Fully charged battery allows up to 300 exposures
- Operator-friendly due to a centered balance point
- Innovative impact resistant construction
- Approx. 240 minutes charging time
- Serial interface for connecting to the digital system (optional)
- Light visor with scale for format adjustment and spirit level and much more

Small, battery-operated X-ray unit Gierth TR 90/20

Scope of delivery

- X-ray machine TR 90/20, including 2 x battery
- Aluminium carrying case
- 2-stage hand trigger switch

Short description

- Battery-powered high-frequency X-ray apparatus
- Only 6.8 kg
- Fully charged battery allows up to 300 shots
- User-friendly centre of gravity
- Approx. 240 minutes charging time
- Serial interface for connection to the digital system (optional)
- Light field indicator with scale for format adjustment and spirit level
- Light field indicator can be activated via manual release
- Battery status indicator
- Acoustic and optical signal when triggered
- 5 Memory - Function keys, dual laser bearing
- Digital display of "X-RAY", "READY" and "ERROR"
- Tape measure for film focus distance measurement
- Aluminum casing

Technical Specifications

Inverter frequency	100 kHz
Power requirement	1.35 kVA
Output in 2-kV Steps	40 – 60 kV = 20 mA (max.) 62 – 80 kV = 15 mA (max.) 82 – 90 kV = 10 mA (max.) 82 – 90 kV = 15 mA (max. in High Power mode)
X-ray tube	Toshiba D - 0814
Focal spot	0.8 mm x 0.8 mm
Weight	6,8 kg including collimator
Dimensions L x W x H	265 mm x 220 mm x 180 mm
Total filtration	2.7 mm Al

Spare battery optionally available

Please visit www.or-technology.com
for more details

Specifications subject to revision without notice

The editor strives to impart correct and up to date information. The provided specifications are based on current knowledge and are subject to revision without notice. This brochure is subject to correction. The editor assumes no responsibility for the information being up to date, correct and complete. All furnished logos, pictures and graphics are property of the particular company and subject to copyright of the licensor. Use, dissemination, distribution or copying of the pictures, logos or text compiled or processed by the editor is subject to our written consent. All rights reserved.



Battery [with charging station]



Headquarters: OR Technology (Oehm und Rehbein GmbH), 18057 Rostock, Germany, Neptunallee 7c
Info-Hotline: +49 381 36 600 600, info@or-technology.com, www.or-technology.com
OR Technology UK: Celtic SMR Ltd., Frederick House, Hayston View, Johnston, Haverfordwest,
Pembrokeshire SA62 3AQ, United Kingdom, www.celticsmr.co.uk, sales@celticsmr.co.uk