

For use in veterinary medicine  
and NDT sector

Order No. AP2600

## The "all-rounder" among universal X-ray units - **GIERTH HF 400 ML**

The very powerful GIERTH HF 400 ML can be used universally as an "all-rounder". The portable monoblock X-ray unit with high-frequency technology is equipped with a dual laser pointer and rotating light field indicator.

The powerful performance of the X-ray machine allows extremely short exposure times and takes portable X-ray imaging to a new level. A serial interface for connecting to a digital system is also available.

- High-frequency X-ray generator with full bridge inverter system
- Weight: 22.4 kg
- Serial interface for connecting with digital radiography systems
- Scaled collimator to adjust the size of the light indicator field
- Light field indicator can be illuminated via the hand switch
- Acoustic and optical timer signal and much more



# The "all-rounder" among universal X-ray units - **GIERTH HF 400 ML**

## Scope of delivery

- X-ray machine Gierth HF 400 ML
- 2-stage hand trigger switch

## Short description

- High-frequency X-ray generator with full bridge inverter system
- Weight: 22.4 kg
- Serial interface for connecting with digital radiography systems
- Collimator with scale to adjust the size of the light field indicator
- Scaled collimator light can be activated via the hand switch
- Acoustic and optical timer signal
- Dual laser pointer
- Digital display „X-RAY“, „READY“ and „ERROR“
- Tape measure for film-focal spot distance
- Aluminium casing

## Technical Specifications

Inverter frequency	50 kHz
Power requirement	6.0 kW
Output in 2-kV Steps	40 - 50 kV = 100 mA (max.) 52 - 60 kV = 80 mA (max.) 62 - 80 kV = 70 mA (max.) 82 - 100 kV = 60 mA (max.) 102 - 120 kV = 40 mA (max.)
X-ray tube	RADIIKL20-1.2-120
Focal spot	1.2 mm x 1.2 mm
Weight	22.4 kg
Dimensions L x W x H	430 mm x 320 mm x 260 mm
Total filtration	2.7 mm Al

Please visit [www.or-technology.com](http://www.or-technology.com) for more details

### Specifications subject to revision without notice

The editor strives to impart correct and up to date information. The provided specifications are based on current knowledge and are subject to revision without notice. This brochure is subject to correction. The editor assumes no responsibility for the information being up to date, correct and complete. All furnished logos, pictures and graphics are property of the particular company and subject to copyright of the licensor. Use, dissemination, distribution or copying of the pictures, logos or text compiled or processed by the editor is subject to our written consent. All rights reserved.

**Headquarters:** OR Technology (Oehm und Rehbein GmbH), 18057 Rostock, Germany, Neptunallee 7c  
**Info-Hotline:** +49 381 36 600 600, [info@or-technology.com](mailto:info@or-technology.com), [www.or-technology.com](http://www.or-technology.com)  
**OR Technology UK:** Celtic SMR Ltd., Frederick House, Hayston View, Johnston, Haverfordwest, Pembrokeshire SA62 3AQ, United Kingdom, [www.celticsmr.co.uk](http://www.celticsmr.co.uk), [sales@celticsmr.co.uk](mailto:sales@celticsmr.co.uk)



Carrying case (optional)

