

For use in veterinary medicine

Order No. AP5500

Portable battery-operated X-ray unit **Amadeo P-125/100 VB**

The 5.6 kW high-performance Amadeo P-125/100VB generator meets a wide range of requirements. The powerful lithium battery provides a long standby mode and ensures multiple exposure modes. The touch screen is simple and uncomplicated to operate.

- kV range in 1 kV steps: 40 to 125 kV
- mAs range 0.1 - 200 mAs
- Dual focus tube, focal spot 0.6 / 1.8 mm
- Rotatable high brightness collimator with integrated timing circuit
- Lithium battery 32.4 V sufficient for approx. 100 shots (50 kV, 80 mA, 20 ms), max. charging time 4h, standby time approx. 7h
- Power 220 - 240 V
- Dimensions 240 x 236 x 449 mm
- Weight 18.6 kg (with battery)



Portable battery-operated X-ray unit Amadeo P-125/100VB

Scope of delivery

- X-ray unit Amadeo P-125/100VB
- Matching and stable transport case
- 2-stage manual release switch

Short description

- Device can be operated with internal battery or external power supply unit
- Max. 100 shots with only one battery charge
- Optimum protection against shocks and external soiling
- Equipped with remote control functions by hand switch
- 1 year manufacturer's warranty incl. X-ray tube and battery

Technical Specifications

Construction	Monoblock X-ray unit with touch panel high frequency technology, optional with Li-Ion battery	
Output range	kV range	40 kV - 125 kV, in 1 kV-Schritten
	mAs range	0.1 mAs - 200 mAs (± 10%, AC operation) 0.1 mAs - 25,0 mAs (± 10%, battery operation)
	mA range	10 mA - 100 mA
	exposure times	0.002 s - 4.0 s
	Output power	max. 5.6 kW (56 mA, 100 kV)
X-ray tube	Tube type	fixed anode
	Focal spots	small 0.6mm ² / large 1.8 mm ²
	Anode angel	15°
Collimator	Light field	43 cm x 43 cm @100 cm SID
	Light source	bright LED, with autotimer integrated, scale length 2,0 m
	SID scale	
Input power	Voltage	AC 220 V ± 10%, single phase
	Frequency	50 Hz ± 1 Hz
	Power	max. 7.0 kW
Weight	18.8 kg (with battery)	
Dimensions	L: 440 mm W: 240 mm H: 236 mm (without retaining bracket)	
Total filtration	≤ 2.5mm Al (inkl. collimator)	
Interface	Serial interface , optional the control of the generator in connection with the digital radiography system is possible	
Battery	Typ	Lithium battery supply
	• for approx. 100 shorts (50 kV, 80 mA, 20 ms)	
	• max. charging time 4h, standby time approx. 7h	

Please visit www.or-technology.com
for more details

Specifications subject to revision without notice

The editor strives to impart correct and up to date information. The provided specifications are based on current knowledge and are subject to revision without notice. This brochure is subject to correction. The editor assumes no responsibility for the information being up to date, correct and complete. All furnished logos, pictures and graphics are property of the particular company and subject to copyright of the licenser. Use, dissemination, distribution or copying of the pictures, logos or text compiled or processed by the editor is subject to our written consent. All rights reserved.

Headquarters: OR Technology (Oehm und Rehbein GmbH), 18057 Rostock, Germany, Neptunallee 7c
Info-Hotline: +49 381 36 600 600, info@or-technology.com, www.or-technology.com
OR Technology UK: Celtic SMR Ltd., Frederick House, Hayston View, Johnston, Haverfordwest, Pembrokeshire SA62 3AQ, United Kingdom, www.celticsmr.co.uk, sales@celticsmr.co.uk

